



ARDEX AF 545

Heavy Duty Epoxy Adhesive

Ultimate Bond Strength - Long term performance and reliability

Water resistant - Suitable in wet operating conditions

Heavy duty grab - Installs difficult coverings

Soft consistency - Easy to mix, trowel and use

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 384 3029
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX AF 545

Heavy Duty Epoxy Adhesive

SPECIAL PROPERTIES

- Ultimate bond strength and dimensional stability
- Resistant to heaving rolling loads
- Works at low temperature
- 100% Solids
- Low odour
- Versatile – bonds to many substrates
- Moisture and alkali resistant

PRODUCT DESCRIPTION

Two part multi purpose epoxy flooring adhesive.

APPLICATION

Internal and external permanent installation.

FLOOR COVERINGS

- Vinyl composition tile (VCT)
- Commercial homogeneous sheet vinyl
- Linoleum
- Rubber tile / Most recycled rubber
- Rubber and vinyl stair treads

IN THE ARDEX SYSTEM

To ensure enhanced performance, reliability and warranty always use ARDEX adhesives within SYSTEMARDEX. Other SYSTEMARDEX products include:

- ARDEX Moisture Barrier
- ARDEX Concrete Sealer
- ARDEX Substrate Primers
- ARDEX Self Levelling and Smoothing Compounds
- ARDEX Finishing Compounds
- ARDEX External Levelling Compounds

SURFACE PREPARATION

All substrates must comply with AS1884. In particular, it must be level, protected from moisture, firm, load-bearing, free from curing compounds, cracks and also have a high tensile and compressive strength and must be prepared accordingly.

SUBSTRATE BONDING GUIDE

- Hardboard underlayment board approved to AS 2458
- Carpet pad underlay
- Cementitious underlayment
- Dry concrete where there is less than 5.5% moisture content or 70% RH

Contact ARDEX Technical Services for other substrates including terrazzo, ceramic tiles and metal substrates.

DIRECTIONS FOR USE

Refer to floor covering manufacturer's instructions.

Condition adhesive and floor coverings to working area temperature 24 hours prior to and 48 hours after installation. Installation temperature of working area and substrate to be a minimum of 10°C and a minimum 30°C.

Add one part Part A into one part Part B (1A:1B) by volume. Mix thoroughly till homogenous in colour and texture. Once mixed the adhesive is ready for immediate use.

Trowel evenly onto substrate avoiding concentrations of adhesive. Install covering immediately into wet adhesive. Cut, fit, position and roll covering within 60 minutes.

SPECIAL INSTALLATION INSTRUCTION

Many recycled rubber contain chemicals that may inhibit bond integrity. If the composition of the recycled rubber is unclear conduct a bond test.

Lightly sand rubber stair treads and clean with white spirits and allow to dry before applying adhesive.

NOTE: Do not reuse container. Dispose of container and adhesive residue in accordance with Federal, State and Local waste disposal regulations. Do not flush adhesive down drains.

SAFETY PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

CAUTION: IRRITANT. Avoid eye and skin contact. If eye contact occurs, flush with water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Keep container closed.

During the installation process, adequate ventilation of the work area should be maintained without causing the entry of contaminants to other parts of building.

Material safety datasheets available upon request, available from the ARDEX website www.ardex.com or from point of sale.

TECHNICAL PROPERTIES

Colour: Part A - Off white
Part B - Light Brown

Priming: If required prime porous substrate with ARDEX P51

Coverage: Using a 0.8 x 1.6 x 2.0mm U-notch trowel approx 6m²/L



Setup Time: Wet set for immediate use

Working Time: 60 minutes varying on substrate, temperature and humidity

Site Variability: Site conditions including porosity, temperature and humidity will alter coverage, tack and working time

Packaging: Kit containing 2.5kg Part A and 2.0kg Part B

Removal:
Wet Clean with warm soapy water
Dry Clean with mineral spirits carefully following warnings on container.

Shelf Life: One year from date of manufacture in unopened container stored at 23°C with less than 50% RH

ARDEX Australia Pty Ltd

NSW Ph (02) 9851 9100 Fax (02) 9838 7970
QLD Ph (07) 3817 6000 Fax (07) 3881 3188
VIC/TAS Ph (03) 9308 9255 Fax (03) 9308 9332
SA Ph (08) 8268 2511 Fax (08) 8345 3207
WA Ph (08) 9256 8600 Fax (08) 9455 1227

ARDEX New Zealand Ltd

Christchurch Ph (03) 3843 029 Fax (03) 3849 779
Auckland Ph (09) 2967 690 Fax (09) 2967 689
Wellington Ph (04) 5685 949 Fax (04) 5686 376

Technical Services Toll Free: 1800 224 070

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

© ARDEX Australia Pty Ltd 2008.

All aforementioned products are the trade marks of ARDEX Australia Pty Ltd, its licensors and affiliates.