



Technical Data Sheet

08/08/2011



Quality
ISO 9001

SOLVENTS / CLEANERS

DESCRIPTION

Bostik manufacture four solvent cleaners. These are used in different situations for different purposes. The range varies in strength and dissolving power.

PROPERTIES

Bostik No. 1 Solvent: Very mild low odour solvent for situations involving polystyrene, or where stains need to be removed from very sensitive plastic surfaces, such as flooring materials. Very fast drying.

Bostik No. 2 Solvent: This is a strong solvent used to thin most contact adhesives, clean brushes or washout spray equipment. It should never be used to clean sensitive surfaces, but is a good degreasing type solvent for metal parts. It is also used to "reactivate" dried adhesive surfaces for re-bonding jobs. Fast drying. It is used also for thinning of contact adhesives or to make up solvent loss from evaporation.

Bostik No. 3 Solvent: This is a mild, fast drying solvent. It is a general purpose de-greasing and cleaning solvent for metals and rubber surfaces. It cannot be used to thin contact adhesives without mixing with No. 2 Solvent.

Bostik No. 4 Solvent: This is a strong solvent used mainly to thin or reactivate urethane or nitrile based adhesives. It can be used to remove dried adhesives from a variety of surfaces. It is sometimes used to clean PVC prior to cementing with adhesives.

PACKAGING

1 litre, 4 litre, 20 litre.

APPLICATION

Bostik solvents are volatile and highly flammable. Please read the Safety Data Sheet (SDS) before using.

Wellington Site (Factory & Admin)
Auckland Site

19 Eastern Hutt Road, Wingate, Lower Hutt
148 Pavilion Drive, Airpark II, Auckland Airport

Ph ++64 4 567 5119
Ph ++64 9 257 5847

Fax ++64 4 567 5412
Fax ++64 9 257 3588

www.bostik.co.nz

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.co.nz

STORAGE

Store in cool, dry conditions out of direct sunlight below 25°C and away from naked flame or sources of heat.

DISPOSAL

If spilt, absorb with clay, sand or earth. Collect and seal in properly labelled metal containers. Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

SHELF LIFE

At least 12 months in original, unopened containers. Unused material must be tightly re-sealed for further storage.

HEALTH AND SAFETY

Fuller details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that the appropriate Safety Data Sheets are read by all concerned. Visit www.bostik.co.nz for copies.

FIRST AID

Swallowed Do not induce vomiting, give a glass of water and contact a doctor immediately.

Skin Remove contaminated clothing, wash with warm soapy water. Do not scrub.

Inhaled Remove person to fresh air. Get medical advice if breathing becomes difficult. If inhaled to excess, remove from contaminated area – apply artificial respiration if not breathing.

Eyes Hold open and flood with water for at least 15 minutes. Get medical advice.

For emergency information contact the National Poisons Information Centre, phone 0800 764 766 (0800 POISON) or CHEMICALL, phone 0800 243 622.

VERSION

Version 4 5th August 2011 Update